

EUROPEAN PATENT OFFICE

Patent Abstracts of Japan

PUBLICATION NUMBER : 2000144041
PUBLICATION DATE : 26-05-00


APPLICATION DATE : 13-11-98
APPLICATION NUMBER : 10322737

APPLICANT : DAINIPPON INK & CHEM INC;

INVENTOR : SAKURAI MIYA;

INT.CL. : C09D135/00 C09D 5/00 // C08F 22/40
C08F290/06

TITLE : ACTIVE ENERGY BEAM CURABLE
COMPOSITION CONTAINING
MALEIMIDE DERIVATIVE FOR
SURFACE COATING OF WOODEN
MATERIAL AND CURING OF THE
COMPOSITION



ABSTRACT : PROBLEM TO BE SOLVED: To obtain an active energy beam curable composition curable with a practical and usual light intensity and exposed dose without using a general-purpose photopolymerization initiator which may cause malodor upon curing, and having excellent adherence to a wooden material by incorporating a maleimide derivative of a specified structure.

SOLUTION: An active energy beam curable composition for surface coating of a wooden material is obtained by containing a maleimide derivative represented by the formula (wherein (m) and (n) are each an integer of 0-6, and m+n is an integer of 1-6; R11 and R12 are each a hydrocarbon bond comprising an aliphatic group or an aromatic group; G1 and G2 are each an ether bond, an ester bond, a urethane bond, and a carbonate bond; R2 is a polyether coupling chain or its residue obtained by bonding an aliphatic group and an aromatic group with an ether linkage, a polyester coupling chain or its residue bound with an ester linkage, a polyurethane coupling chain or its residue bound with a urethane linkage, or a polycarbonate coupling chain or its residue bound with a carbonate linkage, and its average molecular weight is 40-100,000).

COPYRIGHT: (C)2000,JPO